



product
information

6SAP-200 METAL ADHESION PROMOTER

Cardinal's 6SAP-200 is a metal adhesion promoter designed to improve adhesion on metal substrates where adhesion is difficult. 6SAP-200 acts as an intermediate coating between the substrate and the topcoat.

TYPICAL USES:

- Steel substrates
- Copper substrates
- Brass substrates

BENEFITS:

- Easy application

Safety:

Contains organic solvents. Use with adequate ventilation - do not breath vapors or spray mists. If component TLVs are exceeded, a NIOSH approved air supplied respirator is advised. See MSDS for TLV information. Allergic reactions are possible. Avoid use by persons with respiratory problems. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

FIRST AID:

Eye contact, flush immediately with plenty of water for at least 15 min. and get medical attention.

Skin contact, wash thoroughly with soap and water for 5 minutes.

If swallowed, do not induce vomiting and get medical attention immediately.

Inhalation, remove to fresh air.

RELATED PRODUCTS:

PRODUCT NO.	DESCRIPTION / FUNCTION
6S00	1# 2K Polyurethane
6400	2K Polyurethane

FOR INDUSTRIAL USE ONLY
NOT FOR RESIDENTIAL USE

TYPE: Adhesion Promoter

COMPONENTS: One

MINIMUM ORDER: 1 quart

VOC CONTENT: (AS SUPPLIED)

786 GRAMS/LITER (6.55 LBS/GAL)

786 GRAMS/LITER (6.55 LBS/GAL)

VOLUME SOLIDS: 6.4%

FLASH POINT: 24°F TCC

SHELF LIFE: 6 months unopened from date of manufacture on the container.

MIXING RATIO: READY TO SPRAY

APPLICATION: Spray a smooth uniform film.

RECOMMENDED FILM THICKNESS: 0.5 mil

DRY TIME:

Dry to touch Air Dry 15 min.

Recoat, after 30 min.

And before 8 hrs.

(At 1.0 mils dry film thickness, 78° F, 50% RH)

CLEAN-UP: Clean up should be done as soon as possible. Air quality regulations may limit allowable emissions from cleaning operations.

PRODUCT LIMITATIONS:

- For industrial use only.
- Not recommended for exterior applications.

K13TL

So. El Monte, CA 1329 Potrero Ave. 91733 (323) 283-9335 (626) 444-9274 Fax (626) 444-0382

www.cardinalpaint.com

IMPORTANT: Warranty and Disclaimer — The performance characteristics of these products vary according to product application, operating conditions, materials applied to or with and use. Since these factors can affect results, we strongly recommend that you make your own test to determine to your satisfaction whether the product is of acceptable quality, has not been affected by storage or transport and is suitable for your particular purpose under your own operation conditions prior to using any product in full scale production. Seller warrants the products to be free from defects in materials and workmanship. SUCH WARRANTY IS EXCLUSIVE AND IS IN LIEU OF ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OF FITNESS FOR A PARTICULAR PURPOSE. No representative of ours has authority to waive or change this provision, which applies to all sales of these products.

